EGR DECOR

StyleLite®

Waterproof Cabinetry Material Safety Data Sheet

Superior Gloss & Matte Indoor Panels

Australia & New Zealand

September 2025

DISCLAIMER: Information provided in this SDS has been sourced through research or taken directly from the supplier. No in house testing has been conducted on this product.

Section 1 – Identification

Product Name:	StyleLite Waterproof panels
Other Names:	MPB, WCC, WPC panels
Recommended Use:	Decorative panel solution for cabinetry in flood-prone or high-moisture areas.
Description:	Decorative panel with WCC core (WPC) and decorative acrylic surface

SUPPLIER / MANUFACTURE:	
Company Name:	EGR DÉCOR
Address:	45 Machinery St, Darra, QLD, 4076
Telephone No:	+61 7 3718 1100
Email address:	info@egrdecor.com
Website:	www.stylelite.net
In case of emergency:	+61 7 3718 1100

Section 2 – Hazards Identification

The product is a solid composite panel and is considered non-hazardous in its finished form.

Hazard summary (processing risks):

- No significant hazards when handled and used as intended.
- Dust generated during cutting, sanding, or machining may cause mild irritation to the respiratory system, skin, and eyes.
- Combustible under fire conditions; may emit hazardous gases upon combustion.

Signal word: Not applicable for the intact product.

Section 3 – Composition Information on Ingredients

The product is composed of a wood-plastic composite (WPC) core bonded with a decorative acrylic surface using a polyurethane reactive (PUR) adhesive. The exact formulation is proprietary and confidential.

Section 4 – First Aid Measures

In solid form, health hazards and first aid measures are most unlikely. For exposure to dust and fumes from secondary transformation, follow these guidelines:

Inhalation

- If inhaled (dust or fumes), remove victim to fresh air. If breathing is difficult give oxygen. Seek medical attention if symptoms persist or in case of exposure to smoke/fumes from fire.

Skin contact

- If dust gets into eyes, flush with water for at least 15 minutes. Seek medical attention if irritation persists

Skin contact

- For contact with dust, wash skin with soap and water. Remove contaminated clothing and launder before reuse. For burns from molten material, seek immediate medical attention.

Ingestion

- Unlikely for intact panel. If large amounts swallowed, rinse mouth and seek medical advice. Do not induce vomiting unless instructed by medical personnel.

ADVICE TO DOCTOR

Treat symptomatically. Monitor for respiratory irritation or compromise following inhalation of fumes. In case of significant exposure to combustion products, consider evaluation for exposure to carbon monoxide and hydrogen chloride.

Section 5 – Fire Fighting Measures

Suitable extinguishing media

- Water spray (fog), foam, dry chemical or carbon dioxide.

Special protective equipment and precautions for firefighters

- Firefighters should wear full protective clothing and self-contained breathing apparatus.

Hazards from combustion

- When burned, the product may release toxic gases such as carbon monoxide, hydrogen chloride, and other toxic and irritating fumes. Burning panels may drip molten material which can cause burns.

Section 6 – Accidental Release Measures

Personal precautions

- Avoid generating dust. Use appropriate personal protective equipment including dust masks, gloves, and eye protection.

Environmental precautions

- Prevent dust and debris from entering drains, waterways, or soil.

Methods for containment and cleaning up

- Collect large pieces for reuse or disposal. Carefully collect dust and fragments using vacuum extraction or wet methods to minimise dust dispersion. Dispose of waste according to local regulations

Section 7 – Handelling and Storage

Handling

- Avoid generating dust and control dust at the source with local exhaust ventilation. Avoid inhalation of dust and prolonged skin contact with dust. Use appropriate personal protective equipment (PPE). Use safe handling practices to avoid cuts from panel edges.

Storage

- Store in a cool, dry, well-ventilated area away from heat and ignition sources. Keep away from heat, open flame, and direct sunlight. Keep away from strong oxidisers and strong acids. Stack panels on a flat surface to avoid warping. Protect from moisture and physical damage.

Section 8 – Exposure Controls/Personal Protection

Exposure standards

- No specific exposure limits exist for the finished panel. Follow general dust exposure limits where applicable.

Engineering controls

- Use adequate ventilation and dust extraction during cutting/sanding/routing to capture dust and fumes. Enclose processes where practicable. Ensure good general ventilation.

PERSONAL PROTECTIVE EQUIPMENT (PPE)	
Respiratory protection:	P1 or P2 dust mask or respirator when cutting or sanding.
Eye protection:	Safety glasses or goggles; use face shield for heavy dust or molten material risk.
Skin protection:	Cut-resistant gloves and long-sleeved clothing to minimize skin contact with dust.
Other:	Safety footwear.

Section 9 – Physical and Chemical Properties

Appearance:	Solid composite panel.
Odour:	Odourless in normal condition.
pH:	Not applicable.
Solubility in water:	Insoluble.
Density:	Approx. 0.7 g/cm³.
Flammability:	Combustible solid

Section 10 – Stability and Reactivity

Reactivity:

- Stable under normal storage and use conditions.

Incompatible materials:

- Strong oxidisers, strong acids (can accelerate degradation and generate corrosive gases).

Conditions to avoid:

- High temperatures, open flames, incompatible chemicals.

Hazardous decomposition products:

- Hydrogen chloride, carbon monoxide, carbon dioxide, other organochlorine fragments and soot when burned or thermally degraded.

Section 11 – Toxicological Information

The product in its finished form is non-toxic and non-irritating. Ingestion of large fragments is unlikely and would be mechanically obstructive rather than chemically toxic. Dust generated during processing may cause mild mechanical irritation to respiratory tract, skin, or eyes.

Section 12 – Ecological Information

Ecotoxicity:

- Solid is inert and not readily soluble. Small fragments and dust may be physically persistent in the environment and pose ingestion risk to wildlife. Avoid release of dust and debris to waterways.

Bioaccumulative potential:

- Not expected to bioaccumulate, but persistent fragments may physically accumulate.

Persistence and degradability:

- Solid is not readily biodegradable and persists in the environment.

Mobility in soil:

- Insoluble; low mobility.

Section 13 – Disposal Considerations

Dispose in accordance with local regulations. Recycling is preferred where available. Avoid releasing into the environment. Landfill disposal should follow local regulatory requirements for plastics.

Section 14 – Transport Information

Not classified as dangerous goods according to Australian transport regulations.

Section 15 – Regulatory Information

- This product complies with relevant Australian standards and regulations for decorative building materials.
- Exposure to dust and toxic gases generated during processing is subject to Workplace Exposure Standards as per Safe Work Australia guidelines.

Notice to reader:
The information provided in this SDS is believed to be accurate at the time of issue and is based on current knowledge and Australian regulations. It is intended as guidance only. Users should ensure the information is suitable for their specific use and comply with all applicable laws and regulations. The supplier assumes no liability for misuse of the product or reliance on this SDS.

StyleLite®

Waterproof Cabinetry Technical Data Sheet

Revision: 1.0

Australia & New Zealand

1st September 2025

1. EGR expressly disclaims any representations or warranties of any kind, whether express or implied, as to the accuracy, currency, completeness and/or the merchantability or fitness for a particular purpose of any information contained in or provided via this documentation and/or any service or product described or promoted in this document. 2. It is the customer's responsibility to thoroughly examine the product using a qualified person, to determine whether it is suitable for the application it was purchased for. 3. The receiver of our products is fully responsible to check and to take into account possible third party's patent rights, as well as the existing laws in the country of installation prior to installing our product. 4. No liability may be derived from these images or statements nor from our free technical advice. 5. EGR reserves the right to change, add or remove colours or product without notice. 6. EGR Decor and EGR are registered trademarks. 7. Images and colours should be used as a guide only. 8. Ten Year Indoor Warranty: The EGR Decor warranties cover faulty materials for the periods specified on the relevant product warranty documents. The EGR Decor warranties commence from the date of sale by EGR, they are not transferable and are subject to the terms, conditions and exclusions contained within those warranties.

@ Copyright 2024 / Patent Pending Oakmoore Pty Ltd trading as EGR.